



### **Features**

- High efficiency  
economical air consumption
- Simple handling
- Reliable and low-maintenance
- Easy to clean
- Environment friendly  
Pump components made of  
Stainless Steel for operation  
with waterborne spray materials
- Operation of low noise level
- Universally applicable
- 12 months ITW warranty
- ex-proof

### **Range of Application**

- Shipbuilding industry  
and shipyards
- Transportation
- Steel construction
- Off Road
- Commercial vehicles
- Bridge construction
- Tunnel sanitation

### **Suitable for the following materials**

- General coating materials
- 2-K material
- Anticorrosive paint
- Tar-Epoxy paint
- Oil and grease
- Isolation material



## **HP 6/60, HP 20/66 and HP 25/48**

### **The Solution For Protection Against Corrosion**

The HP 6/60, HP 20/66, and HP 25/48 are ideal feed pumps for all markets with the demand for protection against corrosion. They are suitable for all common Airless spray guns and have up to two gun connections. All three pumps are designed for rough continuous operation. They are also suitable for automatic fluid supply systems. The HP 6/60, HP 20/66, and HP 25/48 are available as cart mounted or wall mounted options.



## Specification

	<b>HP 6/60</b>	<b>HP 20/66</b>	<b>HP 25/48</b>
Ratio	60:1	66:1	48:1
Max. Inlet Pressure:	6,5 bar	6,5 bar	8,0 bar
Flow Rate:	6,0 l/min	18,0 l/min	25,0 l/min
Flow Rate Nominal:	2,3 l/min	6,9 l/min	9,0 l/min
Volume/Cycle:	38,0 cm <sup>3</sup>	115,0 cm <sup>3</sup>	150,0 cm <sup>3</sup>
Max. Operating Pressure:	390 bar	429 bar	384 bar
Cylinder Diameter:	140 mm	200 mm	200 mm
Piston Stroke:	75 mm	120 mm	120 mm
Air Consumption:	120 - 1.200 l/min	600- 2.650 l/min	600- 2.650 l/min

## Summary


	<b>HP 6/60 F-AL</b>	<b>HP 6/60 W-AL</b>	<b>HP 20/66 F-AL</b>	<b>HP 20/66 W-AL</b>	<b>HP 25/48 F-AL</b>	<b>HP 25/48 W-AL</b>
Basic Model HP 6/60	●	●				
Basic Model HP 20/66			●	●		
Basic Model HP 25/48					●	●
High Pressure Filter	Type 11*	Type 11*	Type 11*	Type 11*	Type 11*	Type 11*
Cart Mount Type	Type 02		Type 04		Type 04	
Wall Mount Type		Type 02		Type 04		Type 04
Filter Pressure Regulator	1/2"	1/2"	1"	1"	1"	1"
Suction System flex.	NW 20	NW 20	NW 25	NW 25	NW 25	NW 25

\*(Stainless Steel)

### Quality Passport HP-Pumps:

- Modular construction – simple design – easy maintenance – guaranteed high efficiency
- Wetted parts made of Stainless Steel – fixed, spring tension packing • All valves made of hard metal (tungsten carbide) – sealing over disc washer – hard plated double piston
- Return valve in series – standard packing leather / Teflon, optional pure Teflon packing

### Approved Distributor:



### ITW Oberflächentechnik GmbH

Justus-von-Liebig-Str. 31  
D-63128 Dietzenbach  
Tel +49 (0) 60 74/403-1  
Fax +49 (0) 60 74/403-300  
www.itwifeuro.com

### ITW Industrial Finishing

Ringwood Road, Bournemouth,  
Dorset, BH11 9LH, England  
Phone +44 (0) 1202-57 1111  
Fax +44 (0) 1202-590073  
www.itwifeuro.com